

The technical drawing illustrates a bridge deck cross-section with three spans. Key features include:

- Elevation Levels:** +54.40 (top surface), +53.00 (deck top), +52.40 (bottom chord top), and +52.00 (bottom chord bottom).
- Dimensions:** Span lengths are indicated as 9.55m between main supports. Other dimensions include 1.80m, 0.35m, 0.60m, 0.20m, 0.15m, 0.10m, 0.25m, 0.30m, 0.35m, 0.40m, 0.45m, 0.50m, 0.55m, 0.60m, 0.65m, 0.70m, 0.75m, 0.80m, 0.85m, 0.90m, 0.95m, 1.00m, 1.05m, 1.10m, 1.15m, 1.20m, 1.25m, 1.30m, 1.35m, 1.40m, 1.45m, 1.50m, 1.55m, 1.60m, 1.65m, 1.70m, 1.75m, 1.80m, 1.85m, 1.90m, 1.95m, 2.00m, 2.05m, 2.10m, 2.15m, 2.20m, 2.25m, 2.30m, 2.35m, 2.40m, 2.45m, 2.50m, 2.55m, 2.60m, 2.65m, 2.70m, 2.75m, 2.80m, 2.85m, 2.90m, 2.95m, 3.00m, 3.05m, 3.10m, 3.15m, 3.20m, 3.25m, 3.30m, 3.35m, 3.40m, 3.45m, 3.50m, 3.55m, 3.60m, 3.65m, 3.70m, 3.75m, 3.80m, 3.85m, 3.90m, 3.95m, 4.00m, 4.05m, 4.10m, 4.15m, 4.20m, 4.25m, 4.30m, 4.35m, 4.40m, 4.45m, 4.50m, 4.55m, 4.60m, 4.65m, 4.70m, 4.75m, 4.80m, 4.85m, 4.90m, 4.95m, 5.00m, 5.05m, 5.10m, 5.15m, 5.20m, 5.25m, 5.30m, 5.35m, 5.40m, 5.45m, 5.50m, 5.55m, 5.60m, 5.65m, 5.70m, 5.75m, 5.80m, 5.85m, 5.90m, 5.95m, 6.00m, 6.05m, 6.10m, 6.15m, 6.20m, 6.25m, 6.30m, 6.35m, 6.40m, 6.45m, 6.50m, 6.55m, 6.60m, 6.65m, 6.70m, 6.75m, 6.80m, 6.85m, 6.90m, 6.95m, 7.00m, 7.05m, 7.10m, 7.15m, 7.20m, 7.25m, 7.30m, 7.35m, 7.40m, 7.45m, 7.50m, 7.55m, 7.60m, 7.65m, 7.70m, 7.75m, 7.80m, 7.85m, 7.90m, 7.95m, 8.00m, 8.05m, 8.10m, 8.15m, 8.20m, 8.25m, 8.30m, 8.35m, 8.40m, 8.45m, 8.50m, 8.55m, 8.60m, 8.65m, 8.70m, 8.75m, 8.80m, 8.85m, 8.90m, 8.95m, 9.00m, 9.05m, 9.10m, 9.15m, 9.20m, 9.25m, 9.30m, 9.35m, 9.40m, 9.45m, 9.50m, 9.55m, 9.60m, 9.65m, 9.70m, 9.75m, 9.80m, 9.85m, 9.90m, 9.95m, 10.00m, 10.05m, 10.10m, 10.15m, 10.20m, 10.25m, 10.30m, 10.35m, 10.40m, 10.45m, 10.50m, 10.55m, 10.60m, 10.65m, 10.70m, 10.75m, 10.80m, 10.85m, 10.90m, 10.95m, 11.00m, 11.05m, 11.10m, 11.15m, 11.20m, 11.25m, 11.30m, 11.35m, 11.40m, 11.45m, 11.50m, 11.55m, 11.60m, 11.65m, 11.70m, 11.75m, 11.80m, 11.85m, 11.90m, 11.95m, 12.00m, 12.05m, 12.10m, 12.15m, 12.20m, 12.25m, 12.30m, 12.35m, 12.40m, 12.45m, 12.50m, 12.55m, 12.60m, 12.65m, 12.70m, 12.75m, 12.80m, 12.85m, 12.90m, 12.95m, 13.00m, 13.05m, 13.10m, 13.15m, 13.20m, 13.25m, 13.30m, 13.35m, 13.40m, 13.45m, 13.50m, 13.55m, 13.60m, 13.65m, 13.70m, 13.75m, 13.80m, 13.85m, 13.90m, 13.95m, 14.00m, 14.05m, 14.10m, 14.15m, 14.20m, 14.25m, 14.30m, 14.35m, 14.40m, 14.45m, 14.50m, 14.55m, 14.60m, 14.65m, 14.70m, 14.75m, 14.80m, 14.85m, 14.90m, 14.95m, 15.00m, 15.05m, 15.10m, 15.15m, 15.20m, 15.25m, 15.30m, 15.35m, 15.40m, 15.45m, 15.50m, 15.55m, 15.60m, 15.65m, 15.70m, 15.75m, 15.80m, 15.85m, 15.90m, 15.95m, 16.00m, 16.05m, 16.10m, 16.15m, 16.20m, 16.25m, 16.30m, 16.35m, 16.40m, 16.45m, 16.50m, 16.55m, 16.60m, 16.65m, 16.70m, 16.75m, 16.80m, 16.85m, 16.90m, 16.95m, 17.00m, 17.05m, 17.10m, 17.15m, 17.20m, 17.25m, 17.30m, 17.35m, 17.40m, 17.45m, 17.50m, 17.55m, 17.60m, 17.65m, 17.70m, 17.75m, 17.80m, 17.85m, 17.90m, 17.95m, 18.00m, 18.05m, 18.10m, 18.15m, 18.20m, 18.25m, 18.30m, 18.35m, 18.40m, 18.45m, 18.50m, 18.55m, 18.60m, 18.65m, 18.70m, 18.75m, 18.80m, 18.85m, 18.90m, 18.95m, 19.00m, 19.05m, 19.10m, 19.15m, 19.20m, 19.25m, 19.30m, 19.35m, 19.40m, 19.45m, 19.50m, 19.55m, 19.60m, 19.65m, 19.70m, 19.75m, 19.80m, 19.85m, 19.90m, 19.95m, 20.00m, 20.05m, 20.10m, 20.15m, 20.20m, 20.25m, 20.30m, 20.35m, 20.40m, 20.45m, 20.50m, 20.55m, 20.60m, 20.65m, 20.70m, 20.75m, 20.80m, 20.85m, 20.90m, 20.95m, 21.00m, 21.05m, 21.10m, 21.15m, 21.20m, 21.25m, 21.30m, 21.35m, 21.40m, 21.45m, 21.50m, 21.55m, 21.60m, 21.65m, 21.70m, 21.75m, 21.80m, 21.85m, 21.90m, 21.95m, 22.00m, 22.05m, 22.10m, 22.15m, 22.20m, 22.25m, 22.30m, 22.35m, 22.40m, 22.45m, 22.50m, 22.55m, 22.60m, 22.65m, 22.70m, 22.75m, 22.80m, 22.85m, 22.90m, 22.95m, 23.00m, 23.05m, 23.10m, 23.15m, 23.20m, 23.25m, 23.30m, 23.35m, 23.40m, 23.45m, 23.50m, 23.55m, 23.60m, 23.65m, 23.70m, 23.75m, 23.80m, 23.85m, 23.90m, 23.95m, 24.00m, 24.05m, 24.10m, 24.15m, 24.20m, 24.25m, 24.30m, 24.35m, 24.40m, 24.45m, 24.50m, 24.55m, 24.60m, 24.65m, 24.70m, 24.75m, 24.80m, 24.85m, 24.90m, 24.95m, 25.00m, 25.05m, 25.10m, 25.15m, 25.20m, 25.25m, 25.30m, 25.35m, 25.40m, 25.45m, 25

Technical drawing of a drainage system cross-section. The drawing shows a concrete channel with a sloped bottom (Pendenza Fondo Soletta) and a series of square drainage openings (FORI 20x20). The channel is labeled with elevations: 52.40, 53.00, 53.30, 54.40, 53.76, 53.00, 52.50, and 52.00. Dimensions for the channel width (0.30, 0.50, 0.30) and depth (0.64, 0.16, 0.40) are indicated. A note 'Pendenza Fondo Soletta' points to the sloped bottom surface.

The diagram illustrates a cross-section of a wall foundation. The ground level is indicated by a dashed line at elevation $\nabla +53.00$. Above the ground, there are two more levels: $\nabla +54.40$ and $\nabla +53.76$. A horizontal section labeled "FORO PER INGRESSO CANALIZZAZIONI ARIA" is shown at elevation $\nabla +53.76$. To the right, a vertical section labeled "FORO 100x100 PER PORTELLA D'ISPEZIONE" is shown at elevation $\nabla +53.00$. Below the ground level, the foundation is shown with a base at elevation $\nabla +52.40$. On the left side, there are additional levels: $\nabla +52.40$ and $\nabla +52.00$.

GIUNTO CON WATERSTOP IN PVC
TIPO JOINT ACL 440

0.02

Technical drawing of a drainage system showing three sections of a concrete channel. The drawing includes elevations, dimensions, and labels for components like "PORTA IN CEMENTO" and "lastro in c.a. s=4 cm". The channel is shown with a concrete base and a concrete curb. The drawing is divided into three sections by vertical lines, each showing a different part of the system. The first section on the left shows a 250 PVC pipe entering the channel. The middle section shows a concrete curb with a concrete door. The right section shows another concrete curb with a concrete door. The drawing includes various dimensions and elevations to specify the construction.

GOBI 501

▽+53.00

+51.80

ALLA STAZIONE Ø150 PVC
SOLLEVAMENTO PERCOLATO

▽+51.80

▽+51.10

[illegible]

– LA SUPERFICIE INTERNA DOVRA' ESSERE IMPERMEABILIZZATA CON VERNICIATURA EPOSSIDICA CATRAMOSA



Fornitura e posa in opera del materiale biofiltrante a servizio dei biofiltri destinati al trattamento e la deodorizzazione delle arie esauste in uscita dal sistema di lavaggio aria (scrubber) degli impianti TMB di Giugliano in Campania (NA), TMB di Tufino (NA) e STIR di Caivano

AMMINISTRATORE UNICO	dott. Renato Penza
RESPONSABILE TECNICO	ing. Domenico Ruggeri
GRUPPO DI LAVORO	Area Tecnica

Rev.	Data
01	Ottobre 2024
02	Febbraio 2025

	dott. Renato Penza
	ing. Domenico Ru

	Area Tecnica
--	---------------------